

11/22/00



Patent

Attorney's Docket No. 026575-060

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

 UTILITY PATENT
APPLICATION TRANSMITTAL LETTER
**Box PATENT APPLICATION**

Assistant Commissioner for Patents

Washington, D.C. 20231

Sir:

Enclosed for filing is the utility patent application of Noriyuki ICHIKAWA and Takafumi SUMINO for CATHETER AND METHOD FOR MANUFACTURING THE SAME.

Also enclosed are:

- ☒ 3 sheet(s) of ☒ formal ☐ informal drawing(s);
- ☒ a claim for foreign priority under 35 U.S.C. §§ 119 and/or 365 is ☐ hereby made to filed in on ;
- ☒ in the declaration;
- ☒ Claim for Convention Priority
- ☒ a certified copy of the priority document; and One (1) copy of Priority Document;
- ☐ a General Authorization for Petitions for Extensions of Time and Payment of Fees;
- ☐ an Assignment document;
- ☐ an Information Disclosure Statement; and
- ☐ Other:

- ☒ An ☐ executed ☒ unexecuted declaration of the inventor(s)

☒ also is enclosed ☐ will follow.

- ☐ Please amend the specification by inserting before the first line the sentence --This application claims priority under 35 U.S.C. §§ 119 and/or 365 to filed in on ; the entire content of which is hereby incorporated by reference.--
- ☐ A bibliographic data entry sheet is enclosed.
- ☐ Small entity status is hereby claimed.

☒ The filing fee has been calculated as follows ☐ and in accordance with the enclosed preliminary amendment:

**21839**

(11/00)

C L A I M S					
	No. OF CLAIMS		EXTRA CLAIMS	RATE	FEE
Basic Application Fee					\$710.00 (101)
Total Claims	9	MINUS 20 =	0	× \$18.00 (103) =	0
Independent Claims	2	MINUS 3 =	0	× \$80.00 (102) =	0
If multiple dependent claims are presented, add \$270.00 (104)					
Total Application Fee					710.00
If small entity status is claimed, subtract 50% of Total Application Fee					
Add Assignment Recording Fee \$ if Assignment document is enclosed					
TOTAL APPLICATION FEE DUE					710.00

[] This application is being filed without a filing fee. Issuance of a Notice to File Missing Parts of Application is respectfully requested.

[X] A check in the amount of \$ 710.00 is enclosed for the fee due.

[] Charge \$ _____ to Deposit Account No. 02-4800 for the fee due.

[X] The Commissioner is hereby authorized to charge any appropriate fees under 37 C.F.R. §§ 1.16, 1.17 and 1.21 that may be required by this paper, and to credit any overpayment, to Deposit Account No. 02-4800. This paper is submitted in duplicate.

Please address all correspondence concerning the present application to:

Platon N. Mandros
BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

Date: November 22, 2000

By: William C. Rowland RN 30888, for
Platon N. Mandros
Registration No. 22,124

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

0971236.11200

TITLE OF THE INVENTION

CATHETER AND METHOD FOR MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 11-336081, filed November 26, 1999,
the entire contents of which are incorporated herein
by reference.

BACKGROUND OF THE INVENTION

10 The present invention relates to a catheter such
as a vasolidation catheter for dilating a stenosis
within the blood vessel for curing the stenosis so as
to improve the blood flow on the side of the periphery
of the stenosis and a method for manufacturing the
15 particular catheter.

The advent of a microcatheter has made it possible
to perform therapy and diagnosis within a fine blood
vessel or vasalium, though the conventional catheter is
said to be incapable of performing such a therapy and
20 diagnosis. The microcatheter includes, for example,
a percutaneous transluminal coronary angioplasty
catheter, hereinafter referred to as a PCTA dilatation
catheter, used for curing the myocardial infarction or
angina pectris. The PTCA dilatation catheter includes
25 in general an outer tube having an inflation lumen,
an inner tube having a guide wire lumen, an inflatable
member (balloon) bonded in the vicinity of the distal

ends of the inner tube and the outer tube, and a hub mounted to the proximal end portion of the inner tube and the outer tube. As described above, the catheter tube constituting the PTCA dilatation catheter requires at least two lumens. Therefore, a biaxial plastic tube, i.e., a plastic tube having openings in its cross section such as a double lumen, or a plastic tube of a coaxial structure such as a coaxial catheter tube is generally used for the PTCA dilatation catheter.

The PTCA dilation catheter formed of the biaxial catheter tube has an advantage that satisfactory pushability can be obtained. However, the biaxial catheter tube is poor in operability of the guide wire and is not suitable for decreasing the diameter of the catheter tube.

Under the circumstances, a catheter tube of a coaxial structure is mainly used in recent years for forming the PTCA dilatation catheter. The technology for improving trackability and pushability for the catheter of the coaxial structure within the blood vessel is disclosed in, for example, U.S. Patent 5,496,275 and U.S. Patent 5,759,191.

The catheter disclosed in U.S. Patent 5,496,275 is constructed such that an inner tube and an outer tube are bonded to each other over a considerable distance between a position considerably away from a balloon toward the proximal end of the outer tube and the

proximal end of the balloon so as to form a narrowed passageway for balloon inflation fluid. In this construction, it is necessary for the balloon inflation fluid to pass through a narrow fluid passageway from a position considerably in front of the balloon. Therefore, flow of the inflation fluid required for inflating the balloon is obstructed, resulting in a poor response time to inflation and deflation of the balloon.

10 The catheter discloses in U.S. Patent 5,759,191 is constructed such that an inner tube and an outer tube are bonded to each other within a balloon with an annular spacer, and that a small opening is formed through the wall of the outer tube. In this construction, the balloon inflation fluid passes through the small opening made in the wall of the outer tube in a direction perpendicular to the long axis of the shaft so as to be injected into and discharged from the balloon. Therefore, the balloon inflation fluid fails to flow smoothly, resulting in a poor response time to inflation and deflation of the balloon. An additional problem is that, since the inner tube and the outer tube are bonded to each other, a troublesome manufacturing step is required.

25 Further, Japanese Patent Disclosure No. 11-19216 discloses a method of easily bonding an inner tube and an outer tube constituting a catheter tube. In this

05747535-11200

method, the inner tube and the outer tube are formed of compatible materials, and the outer tube is irradiated with a light beam for thermal fusion bonding of the tubes. In the method disclosed in this prior art, a mandrel for retaining a first lumen is inserted into the inner tube, and a mandrel for retaining a second lumen is inserted into the clearance between the inner tube and the outer tube. Under this condition, the outer tube is irradiated with the light beam. The reason that the mandrel for retaining the second lumen is inserted into the clearance between the inner tube and the outer tube is to prevent the second lumen from being blocked by thermal deformation of the inner and outer tubes caused by heat transfer to regions other than the focused region of the light beam. Since it is necessary to insert the mandrel for retaining the second lumen into the clearance between the inner and outer tubes, a troublesome manufacturing step is required in this prior art. In addition, since the outer tube is thermally deformed by the irradiation with the light beam not only on the inner surface but also on the outer surface, the appearance of the catheter is impaired.

BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide a method for manufacturing a catheter, which permits easily bonding the inner tube and the outer tube to

each other in a short time without using a mandrel for retaining a lumen between the inner tube and the outer tube.

Another object of the present invention is to
5 provide a catheter being pushed favorably in the blood vessel, which is free from thermal deformation of the inner tube and the outer tube in regions other than the bonded portion, which is satisfactory in response time to inflation and deflation of the inflatable member
10 because the interruption of the fluid passageway of the inflation fluid and the obstacle to the inflow of the inflation fluid into the inflatable member are negligibly small, and which is satisfactory in the appearance of the outer surface of the outer tube.

15 According to a first aspect of the present invention, there is provided a method for manufacturing a catheter comprising an inner tube forming a first lumen and an outer tube arranged coaxial with the inner tube, a second lumen being formed between the outer
20 surface of the inner tube and the inner surface of the outer tube, comprising steps of: inserting a mandrel for retaining the first lumen into the inner tube; and applying an ultrasonic horn to the outer surface of the outer tube for oscillating ultrasonic waves, thereby
25 fusion bonding the inner surface of the outer tube to the outer surface of the inner tube.

In the method of the present invention, the inner

0971256-11260

surface of the outer tube is fusion bonded to the outer surface of the inner tube by utilizing an ultrasonic oscillation. Therefore, the thermal deformation does not take place in portions other than the bonded portion. In addition, it is unnecessary to use a mandrel for retaining a second lumen between the inner tube and the outer tube during the bonding operation. Since it suffices to perform the fusion bonding operation utilizing an ultrasonic oscillation only with a mandrel for retaining the first lumen inserted into the inner tube as described above, the inner tube and the outer tube are bonded to each other easily and in a short time.

According to another aspect of the present invention, there is provided a catheter, comprising: an inner tube forming a first lumen and having an opening at a distal end; an outer tube arranged coaxially with the inner tube and having a distal end positioned at the proximal side to the distal end of the inner tube, a second lumen being formed between the outer surface of the inner tube and the inner surface of the outer tube; a deflated or folded inflatable member having a distal end portion secured to the inner tube and having a proximal end portion secured to the outer tube, and being in communication with the second lumen at the proximal end portion; a first port having an opening in communication with the first lumen; and a second port

09717236.1.1200

having an opening in communication with the second lumen; wherein a part of the inner surface of the outer tube is fusion bonded to a part of the outer surface of the inner tube by utilizing ultrasonic oscillation.

5 In the catheter of the present invention, only a region corresponding to at most 90% of the wall thickness of each of the outer tube and the inner tube from the bonding surface between the inner surface of the outer tube and the outer surface of the inner
10 tube is thermally deformed. In other words, a region corresponding to at least 10% of the wall thickness of the outer tube from the outer surface of the outer tube and a region corresponding to at least 10% of the wall thickness of the inner tube from the inner surface of
15 the inner tube are scarcely subjected to the thermal deformation. Also, those regions of the outer tube and the inner tube that are away from the bonded region are not subjected to the thermal deformation.

 In the present invention, it is desirable for the
20 bonded portion between the inner surface of the outer tube and the outer surface of the inner tube to be formed over a region corresponding to 5 to 95% of the outer circumferential surface of the inner tube and over a length of 0.3 to 30 mm in the axial direction.

25 In the catheter of the present invention, the inner tube and the outer tube are not thermally deformed in regions other than the bonded portion as

09717236-112200

described above. As a result, the interruption of the fluid passageway of the inflation fluid and the obstacle of the inflow of the inflation fluid into the inflatable member are very small, leading to a good response time to inflation and deflation of the inflatable member. In addition, appearance of the outer surface of the outer tube is kept favorable.

In the catheter of the present invention, the inner tube and the outer tube are fixed to each other at the bonded portion. Thus, the inner tube can be prevented from being bent, curved or twisted inside the outer tube. Therefore, a pushing force imparted to the proximal portion of the catheter is not absorbed by intermediate parts thereof but can be reliably transmitted to the distal end thereof. Thus, the pushability (trackability or travel performance in blood vessel) of the catheter in a blood vessel is preferable.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated

09717236-11200

in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 shows the appearance of a catheter according to the present invention;

FIG. 2 is a cross sectional view showing the distal end section of the catheter shown in FIG. 1;

FIG. 3 is a cross sectional view showing the bonded portion of the inner tube and the outer tube in the catheter shown in FIG. 1;

FIG. 4A shows the appearance directed to the bonding method between the inner tube and the outer tube in the catheter of the present invention;

FIG. 4B is a cross sectional view of the catheter shown in FIG. 4A;

FIG. 5A shows the appearance directed to the bonding method between the inner tube and the outer tube in the catheter of the present invention;

FIG. 5B is a cross sectional view of the catheter shown in FIG. 5A;

FIG. 6A shows the appearance directed to the bonding method between the inner tube and the outer tube in the catheter of the present invention;

FIG. 6B is a cross sectional view of the catheter

09717236-11200

shown in FIG. 6A;

FIG. 7A shows the appearance directed to the bonding method between the inner tube and the outer tube in the catheter of the present invention;

5 FIG. 7B is a cross sectional view of the catheter shown in FIG. 7A;

FIG. 8 is a cross sectional view showing the bonded portion between the outer tube on the side of the distal end and the outer tube on the side of the proximal end;

10 FIG. 9 is a cross sectional view showing a tapered portion of the inner tube;

FIG. 10 is a cross sectional view showing the proximal end portion of the catheter of the present invention; and

15 FIG. 11 shows the small diameter portion of a rigidity imparting body.

DETAILED DESCRIPTION OF THE INVENTION

A catheter of the present invention and a method for manufacturing the catheter will now be described with reference to the accompanying drawings.

Specifically, FIG. 1 shows the appearance of a catheter according to one embodiment of the present invention. FIG. 2 is a cross sectional view showing the distal end section of the catheter shown in FIG. 1, and FIG. 3 is a cross sectional view showing the bonded portion between the inner tube and the outer tube in

0971236-11200

the catheter shown in FIG. 1. Further, FIGS. 4 to 7 show the appearances and the cross sectional views corresponding to respective steps of bonding the inner tube and the outer tube.

5 As shown in FIG. 1, a catheter 1 of the present invention comprises a catheter unit 10 and a branched hub 20 joined to the catheter unit 10. As described in detail herein later, the catheter unit 10 comprises an inner tube 2 forming a first lumen L1, an outer tube
10 3 arranged outside the inner tube 2 to form a second lumen L2 with the inner tube 2, and an inflatable member (balloon) 4. Also, the catheter unit 10 can be classified into a distal end section 10a and a main section 10b. The branched hub 20 includes a first port
15 (guide wire port) 21 having an opening in communication with the first lumen L1 and a second port (injection port) 22 having an opening in communication with the second lumen L2.

The distal end section 10a of the catheter unit
20 10 is described with reference to FIG. 2. The inner tube 2 forms the first lumen L1, and the first lumen L1 is open at the distal end of the catheter unit 10. The outer tube 3 is arranged coaxially with the inner tube 2 and also is arranged such that the distal end of
25 the outer tube 3 is positioned at the proximal side to the distal end of the inner tube 2. The second lumen L2 having a sufficiently large volume is formed between

the inner surface of the outer tube 3 and the outer surface of the inner tube 2.

The inflatable member (balloon) 4 is secured to the distal end portion of the inner tube 2 in its distal end portion and is secured to the distal end portion of the outer tube 3 in its proximal end portion with an adhesive agent or fused thereto. The inner space of the inflatable member 4 is in communication with the second lumen L2 at its proximal end portion.

When the inflatable member 4 is not inflated, the inflatable member 4 is deflated or folded on the outer circumferential surface of the inner tube 2. When the inflatable member 4 is inflated, at least a part of the inflatable member 4 is made cylindrical (or forms a column having a polygonal cross section), making it possible to dilate easily the stenosis of the blood vessel. A marker 5 made of a material having a high capability of forming an X-ray image is formed on the outer surface of the inner tube 2 in a position

corresponding to the central portion in the cylindrical portion of the inflatable member 4. Incidentally, it is possible to form a second marker (not shown) on the outer surface of the inner tube 2 in a position corresponding to the proximal end portion of the cylindrical portion of the inflatable member 4. Further, it is also possible to form two markers on the outer surface of the inner tube 2 in positions corresponding to the

0977236.11200

both ends of the cylindrical portion of the inflatable member 4.

09717235.112200

5 The outer surface of the inner tube 2 and the inner surface of the outer tube 3 are fusion bonded to each other in a position rearward of the proximal end of the inflatable member 4 so as to form a bonded portion 6. Because of fixing the inner tube 2 to the outer tube 3 at the bonded portion 6, the inner tube 2 can be prevented from being bent, curved or twisted inside the outer tube 3. Therefore, a pushing force imparted to the proximal portion of the catheter 1 is not absorbed by intermediate parts thereof but can be reliably transmitted to the distal end thereof. Thus, the pushability (trackability or travel performance in blood vessel) of the catheter 1 in a blood vessel is preferable. Since the bonded portion 6 shown in FIG. 2 is formed rearward of the proximal end portion of the inflatable member 4, the flexibility is not impaired in the portion of the inflatable member 4, making it possible to provide a catheter excellent in pushability into the blood vessel and in trackability.

15

20 Alternatively, it is also possible to allow the outer tube 3 to extend into the inflatable member 4 so as to be bonded to the inner tube 2 in a position forward of the proximal end of the inflatable member 4. FIG. 3 is a cross sectional view showing the outer tube 3 and the inner tube 2 at the position of the bonded portion 6.

25

How to bond the outer tube 3 and the inner tube 2 will now be described with reference to FIGS. 4A to 7B. Each of FIGS. 4A, 5A, 6A and 7A shows the appearance of the distal end section of the catheter. Also, each of
5 FIGS. 4B, 5B, 6B and 7B is a cross sectional view at the position of the bonded portion.

As shown in FIGS. 4A and 4B, a mandrel 51 for retaining the first lumen L1 is inserted into the inner tube 2. It is desirable for the outer diameter
10 of the mandrel 51 to be equal to the inner diameter of the inner tube or smaller by about 0.1 mm than the inner diameter of the inner tube 2. In the present invention, it is unnecessary to use in this step a second mandrel for retaining a second lumen as
15 disclosed in Japanese Patent Disclosure No. 11-19216 referred to previously.

In the next step, as shown in FIGS. 5A and 5B, an ultrasonic horn 52 is applied to the outer surface of the outer tube 3 in a position rearward of the
20 proximal end of the inflatable member 4 with a predetermined pressure, preferably with 50 to 5000 gf. Then, as shown in FIGS. 6A and 6B, ultrasonic waves are oscillated from the ultrasonic horn 52 so as to achieve a fusion bonding between the inner surface of the outer
25 tube 3 and the outer surface of the inner tube 2. In this fashion, the bonded portion 6 is formed as shown in FIGS. 7A and 7B. By fixing the outer surface

09717235.112200

of the inner tube 2 to the inner surface of the outer tube 3 by fusion bonding as described above, it is possible to ensure a sufficient pushability of the catheter into the blood vessel and a sufficient trackability within the blood vessel.

In the ultrasonic bonding employed in the present invention, utilized is the inner heat generation at the contact surface between the inner surface of the outer tube 3 and the outer surface of the inner tube 2. As a result, it is possible to selectively heat only that region which is to be bonded, and the heat is unlikely to be transmitted to other regions. It follows that the thermal deformation takes place in only a region corresponding to at most 90% of the wall thickness of each of the outer tube 3 and the inner tube 2 from the bonded surface in the bonded portion 6. In other words, the thermal deformation is scarcely brought about in a region corresponding to at least 10% of the wall thickness of the outer tube 3 from the outer surface of the outer tube 3 and in a region corresponding to at least 10% of the wall thickness of the inner tube 2 from the inner surface of the inner tube 2. Further, the outer tube 3 and the inner tube 2 are not thermally deformed in regions apart from the bonded portion 6.

What should be noted is that, in the present invention, the lumen is neither blocked nor narrowed,

though the conventional technique of inserting a mandrel for retaining a lumen between the outer tube and the inner tube is not employed. As a result, the cross sectional area of the second lumen L2 in the bonded portion is substantially equal to the cross sectional area of the second lumen L2 in regions other than the bonded portion. It follows that the fluid flow into and out of the inflatable member 4 through the second lumen L2 are carried out satisfactorily. In addition, the appearance of the outer tube 3 is not impaired. Also, since the thermal deformation is small as described above, the conventional technique of using a mandrel for retaining the second lumen need not be employed in the present invention. It follows that the outer tube 3 and the inner tube 2 can be bonded to each other in a very short time.

It is desirable for the bonded portion 6 between the inner surface of the outer tube 3 and the outer surface of the inner tube 2 in 5 to 95% of the circumferential outer surface of the inner tube 2 and over a length of 0.3 to 30 mm in the axial direction.

The construction of that portion of the catheter positioned closer to the proximal end than the portion shown in FIG. 2 will now be described.

As shown in FIG. 8, the outer tube 3 comprises a distal end side outer tube 3a and a main section side outer tube 3a bonded to each other. The distal

end portion of the main section side outer tube 3a constitutes an insertion portion 3c having an outer diameter substantially equal to the inner diameter of the distal end side outer tube 3a. The insertion
5 portion 3c is inserted into the proximal end portion of the distal end side outer tube 3a. Further, as shown in FIG. 1, the distal end side outer tube 3a is tapered into a small diameter on the side of the distal end relative to the bonded portion with the main section
10 side outer tube 3a. A slit 7 is formed spirally in the insertion portion 3c of the main section side outer tube 3a. The slit 7 extends from the distal end or a position slightly rearward of the distal end of the insertion portion 3c to reach a position slightly
15 forward of the proximal end of the insertion portion 3c. A region in which the slit 7 is not formed is included in the proximal end portion of the insertion portion 3c. The distal end side outer tube 3a and the main section side outer tube 3a are fixed in the region
20 in which the slit 7 is not formed, and the distal end side outer tube 3a and the main section side outer tube 3a are not fixed in the slit-forming region. If the particular slit 7 is formed, the bonded portion is made flexible so as to permit the distal end portion of the
25 main section side outer tube 3b to be bent more naturally. As a result, the operability of the catheter is more improved. Incidentally, it is

10971236.11200

possible to form a large number of fine holes in place of the slit 7.

As shown in FIG. 9, the inner tube 2 comprises a tapered portion in a position slightly rearward of the bonded portion between the distal end side outer tube 3a and the main section side outer tube 3a. The distal end portion of the inner tube 2 relatively to the tapered portion has a small diameter and the portion on the side of the main section has a diameter larger than that on the side of the distal end.

The proximal end portion of the catheter 1 of the present invention is shown in detail in FIG. 10. A branched hub 20 is fixed to the proximal end portion of the catheter unit 10. The branched hub 20 includes the first port (guide wire port) 21 having an opening in communication with the first lumen L1 and the second port (injection port) 22 having an opening in communication with the second lumen L2.

The proximal end portion of the outer tube 3 is covered with a tube 23 for preventing the bending. The bending preventing tube 23 is formed by covering the proximal end portion of the outer tube 3 with a tube of a thermally shrinkable resin having an inner diameter slightly smaller than the outer diameter of the outer tube 3 after the thermal shrinkage, followed by blowing a hot air against the thermally shrinkable tube so as to heat and thermally shrink the tube. The bending

09717235-112200

preventing tube 23 is fixed by pushing a stopper pin 24 into a projection 22a formed in the inner surface of the second port 22. To be more specific, the stopper pin 24 having an enlarged proximal end portion is inserted into the proximal end of the outer tube 3, and the proximal end of the outer tube 3 is inserted into the distal end portion of the second port 22 until the proximal end portion of the stopper pin 24 is pushed over the projection 22a so as to fix the bending preventing tube 23. In this case, it is possible to coat the contact surface between the second port 22 and the bending preventing tube 23 with an adhesive so as to fix the bending preventing tube 23.

Likewise, the proximal end portion of the inner tube 2 is covered with a tube 25 for preventing the bending. The bending preventing tube 25 is formed by covering the proximal end portion of the inner tube 2 with a tube of a thermally shrinkable resin having an inner diameter slightly smaller than the outer diameter of the inner tube 2 after the thermal shrinkage, followed by blowing a hot air against the thermally shrinkable tube so as to heat and thermally shrink the tube. The bending preventing tube 25 is fixed by pushing a stopper pin 26 into a projection 21a formed in the inner surface of the first port 21. To be more specific, the stopper pin 26 having an enlarged proximal end portion is inserted into the proximal end

0977235.112200

of the inner tube 2, and the proximal end of the inner tube 2 is inserted into the distal end portion of the first port 21 until the proximal end portion of the stopper pin 26 is pushed over the projection 21a so as to fix the bending preventing tube 25. In this case, it is possible to coat the contact surface between the first port 21 and the bending preventing tube 25 with an adhesive so as to fix the bending preventing tube 25.

Also, the distal end portion of the first port 21 is inserted into the proximal end of the second port 22 so as to permit the first port 21 and the second port 22 to be engaged with each other. In this case, the contact surface between the first port 21 and the second port 22 is coated with an adhesive so as to permit the first port 21 and the second port 22 to be fixed to each other without fail.

Incidentally, the construction of the proximal end portion of the catheter 1 of the present invention is not limited to the construction shown in FIG. 10. For example, it is possible to mount in a fluid-tight fashion a tube having a port member to each of the proximal end of the inner tube 2 and the proximal end of the outer tube 3 in place of mounting the branched hub 20.

As shown in FIGS. 8 to 10, a rigidity imparting body 8 made of a metal wire is inserted into the second

09717236.1.2000

lumen L2 defined between the inner tube 2 and the outer tube 3 over a region ranging between the proximal end portion of the branched hub 20 and the distal end section 10a of the catheter unit 10. The rigidity imparting body 8 is intended to prevent the catheter unit 10 from being bent excessively in the bent portion without unduly lowering the flexibility of the catheter and is also intended to facilitate the pushing of the distal end section of the catheter.

5
10 The proximal end portion of the rigidity imparting body 8 is fixed to the outer surface of the proximal end portion of the inner tube 2 by the bending preventing tube 25 covering the proximal end portion of the inner tube 2. Incidentally, it is possible to fix
15 the proximal end portion of the rigidity imparting body 8 to the inner surface of the proximal end portion of the outer tube 3. It should be noted that the rigidity imparting body 8 is not fixed in portions other than the proximal end portion.

20 As shown in FIG. 11, the distal end portion of the rigidity imparting body 8 is made thinner than the other portion. The distal end portion is processed by the method of, for example, polishing. As shown in FIG. 8, the distal end of the thin portion of the
25 rigidity imparting body 8 extends to reach a region in the vicinity of the distal end portion of the main section side outer tube 3a. It is possible for the

0977235-11200

distal end of the thin portion of the rigidity imparting body 8 to extend to reach a region in the vicinity of the distal end of the distal end side outer tube 3a.

5 As described above, the rigidity imparting body 8 is not fixed in the region other than the proximal end portion and, thus, can be moved relatively freely within the second lumen L2. If the rigidity imparting body 8 is movable within the second lumen L2, it is possible to prevent the catheter unit 10 from winding within the blood vessel. As a result, the pushing force imparted to the proximal end of the catheter unit 10 is prevented from being absorbed in the winding portion, which makes it possible to transmit the pushing force to the distal end of the catheter without fail. It follows that the operability of the catheter can be improved. In particular, it is possible to facilitate the pushing operation of the distal end section of the catheter, in which the inflatable member 4 is bonded, into the stenosis of the blood vessel. It is also possible to insert the distal end section of the catheter into the marked stenosis within the blood vessel (sub-complete obturation).

25 In order to obtain a good operability described above, it is desirable for the proximal end portion of the rigidity imparting body 8 to be more rigid than the distal end portion. If the cross sectional area of the

00717236-112200

proximal end portion of the rigidity imparting body 8 is larger than that of the distal end portion, the proximal end portion is made more rigid than the distal end portion. Also, a higher flexibility and a higher rigidity can be imparted to the distal end portion and the main portion, respectively, of the rigidity imparting body 8 by bringing about a temperature gradient in the annealing after the cold working of the metal wire used as the rigidity imparting body 8 such that the temperature is made higher on the distal end side and lower on the main portion side. It is also possible to use a stranded wire prepared by stranding a plurality of thin wires as the rigidity imparting body 8.

The materials, sizes, etc., of the constituents of the catheter of the present invention will now be described.

The inner tube 2 is formed of a material that is flexible to some extent including, for example, polymer materials such as polyolefin (e.g., polyethylene, polypropylene, polybutene, ethylene-propylene copolymer, ethylene-vinyl acetate copolymer, ionomer and a mixture of at least two kinds of them), cross-linked polyolefin, polyvinyl chloride, polyamide, polyamide elastomer, polyester, polyester elastomer, polyurethane, polyurethane elastomer, polyimide, fluoroplastic, and a mixture thereof.

The inner tube 2 has a length of 300-2000 mm, more preferably 300-1500 mm, and a wall thickness of 10-150 μm , more preferably 20-100 μm . The outer diameter of the inner tube 2 is designed to

5 0.30-2.00 mm, preferably 0.40-1.80 mm, on the distal end side, and to 0.40-2.50 mm, preferably 0.55-2.40 mm, on the main section side. Further, the outer diameter of the inner tube 2 may be designed to 0.1-1.0 mm, preferably 0.3-0.7 mm, at the most distal end.

10 The inner tube having different diameters as above can be prepared by any method, for example, by individually forming the inner tubes of the distal end the side and the proximal end side, respectively, followed by bonding them, by applying a secondary

15 processing such as pull-down, or by making the diameter on the distal end side smaller than that on the proximal end side by extrusion.

The material of the outer tube should be capable of ultrasonic bonding with the inner tube and should

20 be flexible to some extent. The materials for the outer tube include, for example, polymer materials such as polyolefin (e.g., polyethylene, polypropylene, polybutene, ethylene-propylene copolymer, ethylene-vinyl acetate copolymer, ionomer and a mixture of at

25 least two kinds of them), cross-linked polyolefin, polyvinyl chloride, polyamide, polyamide elastomer, polyester, polyester elastomer, polyurethane,

09717236.112200

polyurethane elastomer, fluoroplastic, polyimide and a mixture thereof. It is desirable for the material of the outer tube to be equal to the material of the inner tube.

5 Where the outer tube 3 is prepared by bonding the distal end side outer tube 3a and the main section side outer tube 3b, it is possible for these tubes to be made of different materials. For example, it is desirable to use a material having a high rigidity such
10 as a polyimide-based resin for forming the main section side outer tube 3b, and to use a material having flexibility, compared with the material of the tube 3b, such as a polyamide-based resin for forming the distal end side outer tube 3a.

15 The outer tube 3 has a length of 300-2000 mm, preferably 300-1500 mm, and a wall thickness of 25-200 μ m, preferably 50-100 μ m. The outer diameter of the outer tube 3 is designed to 0.50-1.5 mm, preferably 0.60-1.1 mm, in the small diameter portion
20 of the distal end side outer tube 3a, and to 0.75-1.5 mm, preferably 0.9-1.1 mm in the proximal end portion of the distal end side outer tube 3a and in the main section side outer tube 3a.

25 It is desirable for the inflatable member 4 to be made of a material capable of dilating the stenosis of the blood vessel and having flexibility to some extent. The materials for the inflatable member 4 include, for

09717236-11200

example, polyolefin (e.g., polyethylene, polypropylene, polybutene, ethylene-propylene copolymer, ethylene-vinyl acetate copolymer, ionomer and a mixture of at least two kinds of them), cross-linked polyolefin, polyester such as polyethylene terephthalate, polyester elastomer, polyvinyl chloride, polyurethane, polyurethane elastomer, polyphenylene sulfide, polyamide, polyamide elastomer, fluoroplastic, silicone rubber and a latex rubber. It is also possible to use a laminated film prepared by suitably laminating these materials.

The outer diameter of the cylindrical portion of the inflatable member 4 when inflated is 1.0-10 mm, preferably 1.0-5.0 mm. The length of the cylindrical portion of the inflatable member 4 is 5-50 mm, preferably 10-40 mm. Further, the entire length of the inflatable member 4 is 10-70 mm, preferably 15-60 mm.

It is desirable for the marker 5 to be made of a material having a high capability of forming an X-ray image including, for example, Pt, Pt alloy, W, W alloy, Au, Au alloy, Ir, Ir alloy, Ag and Ag alloy. It is desirable for the marker 5 to be formed in the shape of a coil spring or a ring.

It is desirable for the branched hub 20 including the first port 21 and the second port 22 to be made of a thermoplastic resin such as polycarbonate, polyamide, polysulfone, polyarylate, or

09717236.112200

methacrylate-butylene-styrene terpolymer.

It is desirable for the rigidity imparting body 8 to be made of an elastic metal such as stainless steel or a superelastic alloy. In particular, it is desirable to use a high tensile stainless steel, which is generally used for manufacturing a spring, and a Ni/Ti alloy wire, which has superelasticity for forming the rigidity imparting body 8.

The diameter of the rigidity imparting body 8 is designed to 0.05-1.5 mm, preferably 0.10-1.0 mm. Where the diameter of the rigidity imparting body 8 is made smaller on the distal end side, it is desirable for the outer diameter of the small diameter portion to be about 1/5 to 1/10 the outer diameter on the proximal end side.

The catheter of the present invention is not limited to a so-called over-the-wire type described above. It is also possible for the catheter of the present invention to be of a so-called rapid exchange type, in which the first port is disposed on the distal end side relatively to the hub. Also, it is desirable to apply a treatment to impart lubricating properties to the outer surfaces of the outer tube 3 and the inflatable member 4 in order to facilitate the insertion of the catheter 1 into a blood vessel or into a guide catheter. The lubricating treatment can be applied by means of coating of a hydrophilic polymer

09717236.11200

such as poly(2-hydroxyethyl methacrylate),
polyhydroxyethyl acrylate, hydroxypropyl cellulose,
methyl vinyl ether-maleic anhydride copolymer,
polyethylene glycol, polyacrylamide or polyvinyl
5 pyrrolidone, or by means of coating or fixation of
a material satisfactory in lubricity such as a reactive
silicone resin having polydimethyl siloxane on the main
chain.

Additional advantages and modifications will
10 readily occur to those skilled in the art. Therefore,
the invention in its broader aspects is not limited to
the specific details and representative embodiments
shown and described herein. Accordingly, various
modifications may be made without departing from the
15 spirit or scope of the general inventive concept as
defined by the appended claims and their equivalents.

09747235.1.12200

WHAT IS CLAIMED IS:

1. A method for manufacturing a catheter
comprising an inner tube forming a first lumen and
an outer tube arranged coaxially with the inner tube,
5 a second lumen being formed between the outer surface
of the inner tube and the inner surface of the outer
tube, comprising steps of:

inserting a mandrel for retaining the first lumen
into the inner tube; and
10 applying an ultrasonic horn to the outer surface
of the outer tube for oscillating ultrasonic waves,
thereby fusion bonding the inner surface of the outer
tube to the outer surface of the inner tube.

2. The method according to claim 1, wherein each
15 of the inner tube and the outer tube is made of a
polymer material.

3. The method according to claim 2, wherein each
of the inner tube and the outer tube is made of the
same polymer material.

20 4. A catheter, comprising:

an inner tube forming a first lumen and having
an opening at a distal end;
an outer tube arranged coaxially with the inner
tube and having a distal end positioned at the proximal
25 side to the distal end of the inner tube, a second
lumen being formed between the outer surface of the
inner tube and the inner surface of the outer tube;

09717235-112200

09717236-11200

a deflated or folded inflatable member having
a distal end portion secured to the inner tube and
having a proximal end portion secured to the outer
tube, and being in communication with the second lumen
5 at the proximal end portion;

a first port having an opening in communication
with the first lumen; and

a second port having an opening in communication
with the second lumen;

10 wherein a part of the inner surface of the outer
tube is fusion bonded to a part of the outer surface
of the inner tube by the method defined in claim 1.

5. The catheter according to claim 4, wherein,
in the bonded portion between the inner surface of the
15 outer tube and the outer surface of the inner tube,
only that region which corresponds to at most 90% of
the wall thickness of each of the outer tube and the
inner tube from the bonded surface is thermally
deformed.

20 6. The catheter according to claim 4, wherein the
bonded portion between the inner surface of the outer
tube and the outer surface of the inner tube is formed
in 5 to 95% of the circumferential outer surface of the
inner tube.

25 7. The catheter according to claim 4, wherein the
bonded portion between the inner surface of the outer
tube and the outer surface of the inner tube is formed

over a length of 0.3 to 30 mm in the axial direction.






8. The catheter according to claim 4, wherein each of the inner tube and the outer tube is made of a polymer material.

5 9. The catheter according to claim 8, wherein each of the inner tube and the outer tube is made of the same polymer material.

0071236-11200

ABSTRACT OF THE DISCLOSURE

For manufacturing a catheter having an inner tube forming a first lumen and an outer tube arranged coaxially with the inner tube, a second lumen being
5 formed between the inner tube and the outer tube, a mandrel is inserted for retaining the first lumen into the inner tube, and an ultrasonic horn is applied to the outer surface of the outer tube for oscillating ultrasonic waves, thereby fusion bonding the inner
10 surface of the outer tube to the outer surface of the inner tube. The particular method permits easily bonding the inner tube and the outer tube to each other. Also, since thermal deformation is small, it is possible to manufacture a catheter, in which the
15 obstacle to the inflow of the inflation fluid into the inflatable member is very small, and which exhibits a rapid response to inflation and deflation of the inflatable member.






FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B

FIG. 8




FIG. 9





FIG. 10




FIG. 11

**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR UTILITY PATENT APPLICATION**

Attorney's Docket No.

026575-060

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I BELIEVE I AM THE ORIGINAL, FIRST AND SOLE INVENTOR (if only one name is listed below) OR AN ORIGINAL, FIRST AND JOINT INVENTOR (if more than one name is listed below) OF THE SUBJECT MATTER WHICH IS CLAIMED AND FOR WHICH A PATENT IS SOUGHT ON THE INVENTION ENTITLED:

CATHETER AND METHOD FOR MANUFACTURING THE SAME

the specification of which

(check one)



is attached hereto;



was filed on _____ as

Application No. _____

and was amended on _____;
(if applicable)

I HAVE REVIEWED AND UNDERSTAND THE CONTENTS OF THE ABOVE-IDENTIFIED SPECIFICATION, INCLUDING THE CLAIMS, AS AMENDED BY ANY AMENDMENT REFERRED TO ABOVE;

I ACKNOWLEDGE THE DUTY TO DISCLOSE TO THE OFFICE ALL INFORMATION KNOWN TO ME TO BE MATERIAL TO PATENTABILITY AS DEFINED IN TITLE 37, CODE OF FEDERAL REGULATIONS, Sec. 1.56 (as amended effective March 16, 1992);

I do not know and do not believe the said invention was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to said application; that said invention was not in public use or on sale in the United States of America more than one year prior to said application; that said invention has not been patented or made the subject of an inventor's certificate issued before the date of said application in any country foreign to the United States of America on any application filed by me or my legal representatives or assigns more than twelve months prior to said application;

I hereby claim foreign priority benefits under Title 35, United States Code Sec. 119 and/or Sec. 365 of any foreign application(s) for patent or inventor's certificate as indicated below and have also identified below any foreign application for patent or inventor's certificate on this invention having a filing date before that of the application(s) on which priority is claimed:

COMBINED DECLARATION AND POWER OF ATTORNEY	Attorney's Docket No.
	026575-060

COUNTRY/INTERNATIONAL	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED
JAPAN	11-336081	26 11 99	YES <u>X</u> NO <u> </u>
			YES <u> </u> NO <u> </u>

I hereby appoint the following attorneys and agent(s) to prosecute said application and to transact all business in the Patent and Trademark Office connected therewith and to file, prosecute and to transact all business in connection with international applications directed to said invention:

William L. Mathis	17,337	R. Danny Huntington	27,903	Gerald F. Swiss	30,113
Robert S. Swecker	19,885	Eric H. Weisblatt	30,505	Charles F. Wietand III	33,096
Platon N. Mandros	22,124	James W. Peterson	26,057	Bruce T. Wieder	33,815
Benton S. Duffett, Jr.	22,030	Teresa Stanek Rea	30,427	Todd R. Walters	34,040
Norman H. Stepano	22,716	Robert E. Krebs	25,885	Ronni S. Jillions	31,979
Ronald L. Grudziecki	24,970	William C. Rowland	30,888	Harold R. Brown III	36,341
Frederick G. Michaud, Jr.	26,003	T. Gene Dillahunty	25,423	Allen R. Baum	36,086
Alan E. Kopecki	25,813	Patrick C. Keane	32,858	Steven M. duBois	35,023
Regis E. Slutter	26,999	B. Jefferson Boggs, Jr.	32,344	Brian P. O'Shaughnessy	32,747
Samuel C. Miller, III	27,360	William H. Benz	25,952	Kenneth B. Leffler	36,075
Robert G. Mukai	28,531	Peter K. Skiff	31,917	Fred W. Hathaway	32,236
George A. Hovaneec, Jr.	28,223	Richard J. McGrath	29,195		
James A. LaBarre	28,632	Matthew L. Schneider	32,814		
E. Joseph Gess	28,510	Michael G. Savage	32,596		



21839

and: _____

Address all correspondence to:



21839

Platon N. Mandros
BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404

Address all telephone calls to: Platon N. Mandros at (703) 836-6620.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST INVENTOR		SIGNATURE	DATE
Noriyuki ICHIKAWA			
RESIDENCE		CITIZENSHIP	
Fujinomiya-shi; Shizuoka-ken, Japan		Japan	
POST OFFICE ADDRESS			
c/o Terumo Kabushiki Kaisha, 150, Maimaigicho, Fujinomiya-shi, Shizuoka-ken, Japan			
FULL NAME OF SECOND JOINT INVENTOR, IF ANY		SIGNATURE	DATE
Takafumi SUMINO			
RESIDENCE		CITIZENSHIP	
Fujinomiya-shi; Shizuoka-ken, Japan		Japan	
POST OFFICE ADDRESS			
c/o Terumo Kabushiki Kaisha, 150, Maimaigicho, Fujinomiya-shi, Shizuoka-ken, Japan			